

Rugged Tablet PC **SR800**

10.4" XGA (1024x768) 4:3 resolution for industry. PCMCIA / CF Card slots. Digitizer.

RUGGEDBOOK Tablet PC SR800 takes the best aspects of the tablet PC technology and improves it for high-performance mobile applications. Ideal industries are field service, public safety, construction, logistics, law enforcement, military, social welfare, transportation, health care, and hospitality.

SR800 is designed to meet the mobile computing needs and form-factor requirements of on-the-go professionals. Moreover, the rugged design of IP54 can resist against various conditions such as shock, vibration, spill, dust and dirt, hot, and damp. In addition, the magnesium enclosure is employed especially for harsh environments and physical stresses.



MIL-STD
810F

IP54

PCMCIA
CF Card slots

Digitizer

resolution
1024x768

Solution for

- Field Service
- Health Care
- Hospitality
- Logistic
- Transportation
- Utility



Rugged Tablet PC SR800



CPU	Intel® Core Duo 1.2GHz (U2500) CPU Intel® 945GME chipset
LCD Panel	10.4" XGA (1024x768) TFT LCD with resistive touch control panel Optional: Outdoor readable display Optional: Dual mode resistive & digitizer touch panel
Memory & Storage	1GB RAM (up to 2GB max) Shock proof mounted, 2.5" 250GB HDD
Audio	Internal microphone and speaker
Interface	2 x USB 2.0 port 1 x Mini USB 2.0 port 1 x RS-232 port 1 x DC-In jack 1 x Microphone 1 x Earphone 1 x RJ-11 1 x RJ-45 1 x Docking connector
Expansion Slots	1 x PCMCIA Type II slot 1 x Compact Flash Type II slot
Buttons	Five-way control key and four button key Reset button Digitizer/ resistive Switch Power button WiFi /BT switch Screen Rotate hotkey Function hotkey SAS/ESC
Wireless	Integrated WiFi 802.11 a/b/g Bluetooth 2.0 Class I + EDR
Power Supply	Input: 100V-240V, 50-60Hz Output: 20V/65W Li-Ion Battery 7200mAh Max. 7 hours in normal usage
Software	Windows XP Tablet PC Edition
Durability Features	IP54, MIL-STD-810F
Operating Temperature	Operating: -20°C to + 60°C ; Storage: -20°C to +70°C Cold boot: 0°C (battery > 75% charge)
Dimension & Weight	284 x 209 x 63 mm 2.2 kgs
Certification	CE FCC TUV cUL CB BSMI
Accessories	Power adapter Power cord Stylus Service DVD
Warranty	1 yr up to 3yrs limited warranty

Factory Options

2GB SDRAM
Outdoor-view display
Dual mode resistive & digitizer touch panel

Accessory Options

Li-Ion battery 7200mAh
AC power adapter Input 100-240V, Output: 20V/65W
Stylus (for resistive)
Stylus (for WACOM)
Vehicle mounting kit
Car adapter Input 11V-27V, Output: 20V DC
Docking station (2x USB 1.1, 1x RJ45
-1x RS232, 1x DC-IN, docking connector)
Carry bag with carry belt
Carry belt only
Anti-scratch surface film

